

USSR/General Problems of Pathology - Tumors. Experimental
Therapy.

U

Abs Jour : Ref Zhur Biol., No 5, 1959, 22806

Author : Gluzman, F.A.

Inst :

Title : The Influence of Various Methods of Hypothermia on the
Development of Experimental New Formation.

Orig Pub : Vrachebn. delo, 1957, No 12, 1341-1342

Abstract : The experiments were conducted on the rabbit carcinoma
of Brown-Pierce, rats' tumors and induced carcinoma of
mice, induced by 9, 10-dimethyl-1,2-benzanthracene. It
was noted that in hypothermia by means of ether and ice,
the growth of transplanted tumors and induced carcinoma
of the skin is retarded and metastasing decreases. In
early removal of the tumor the degree of development of
recurrences is smaller. In hypothermia according to the
method of Dzhiayya (carbon dioxide and cold), during the

Card 1/2

- 21 -

GLUZMAN, F.A. [Hluzman, F.A.], dots.

Hibernation therapy in the case of premature infants; a survey of the literature. Ped., akush. i gin. 19 no.3:60-61 '57. (MIRA 13:1)

1. Kafedra patologicheskoy fiziologii (sav. - deystvitel'nyy chlen AMN USSR prof. M.M. Sirotinin) Kiyevskogo ordena Trudovogo Krasnogo Znameni meditsinskogo instituta im. akad. A.A. Bogomol'tsa (direktor - dots. I.P. Alekseyenko).

(INFANT (PREMATURE)--CARE AND HYGIENE) (HIBERNATION, ARTIFICIAL)

GLUZMAN, F.A., dotsent, red.; LIKHTENSHTEYN, Ye.I., red.; LIKHTENSHTEYN,
A.D., tekhnred.

[Physiology and pathology of the cardiovascular system in
clinical treatment and experiment; a collection of papers]
Fiziologiya i patologiya serdechno-sosudistoi sistemy v
klinike i eksperimente; sbornik trudov. Kiev, Gos.med.
izd-vo USSR, 1958. 444 p. (MIRA 12:6)

1. Kiev. Meditsinskiy institut.
(CARDIOVASCULAR SYSTEM--DISEASES)

GLUZMAN, F. A., Doc Med Sci (diss) -- "Problems of the reactivity of the organism in malignant growth". Kiev, 1959. 30 pp (Kiev Order of Labor Red Banner Med Inst im Acad A. A. Bogomolets), 250 copies (KL, No 22, 1959, 120)

GLUZMAN, F.A., dotsent

Hypophysis-adrenal cortex system and malignant growth. Vrach.
delo no.2:165-167 F '59. (MIRA 12:6)

1. Kafedra patologicheskoy fiziologii (zav. - deystv.chlen
AMN SSSR, prof.N.N.Sirotinin) Kiyevskogo meditsinskogo
instituta.

(PITUITARY BODY) (ADRENAL CORTEX) (CANCER)

PEYSAKHOVICH, Iosif Mironovich, prof.; KOL'NER, Rakhil' Yul'yevna; KORENEV-SKIY, Leonid Ivanovich; LEVCHUK, Georgiy Antonovich; MAZURENKO, Nikolay Petrovich; POLONSKIY, Boris Leonidovich; SAVITSKIY, Vasilii Nikolayevich; TELEGATOR, Yakov Moiseyevich; UMANSKIY, Yulian Aleksandrovich; GLUZMAN, F.A., red.; RAYZ, A.L., tekhn. red.

[Drug therapy for malignant tumors] Khimioterapiia zlokachestvennykh opukholei. Kiev, Gos. med. izd-vo USSR, 1961. 304 p.

(MIRA 14:11)

(CANCER)

GLUZMAN, F.A. [Hluzman, F.A.]

Effect of cortisone on connective tissues in case of
malignant growths. Fiziol. zhur. [Ukr.] 7 no.6:824-829
N-D '61. (MIRA 15:3)

1. Kafedra patologicheskoy fiziologii Kiyevskogo meditsinskogo
instituta im. akad. A.A. Bogomol'tsa.

(CORTISONE)
(CONNECTIVE TISSUES)
(CANCER)

FEDOROV, Ivan Ignat'yevich, prof.; SIROTIN, N.N., prof., retsenzent;
GLUZMAN, F.A., red.; GITSHEYN, A.D., tekhn. red.; CHUCHUPAK,
V.D., tekhn. red.

[Principles of pathological physiology] Osnovy patologicheskoi
fiziologii. Kiev, Gosmedizdat, USSR, 1962. 385 p.
(MIRA 15:6)

1. Akademiya meditsinskikh nauk JSSR (for Sirotin).
(PHYSIOLOGY, PATHOLOGICAL)

KAVETSKIY, Rostislav Yevgen'yevich[Kavetskyi, R.E.]; GLUZMAN, F.A.,
red.; RAYZ, A.L., tekhn. red.

[Tumor and the body]Opukhol' i organizm. Kiev, Gosmedizdat
USSR, 1962. 298 p. (MIRA 15:9)
(ONCOLOGY)

PLOTICHER, Sarra Moiseyevna; GLUZMAN, F.A., red.; CHUCHEPAK, V.D.,
tekhn. red.

[Diagnostic laboratory studies] Laboratornye diagnosticheskie
issledovaniia. Kiev, Gosmedizdat USSR, 1962. 520 p.
(MIRA 16:12)

(DIAGNOSIS)

GLUZMAN, G.

This is real news! Mest.prom.i khud. promys. 3 no.1:10 Ja '63.
(MI:IA 16:2)

1. Starshiy inzhener Kiyevskogo proyektno-konstruktorskogo byuro
gorodskogo upravleniya bytovogo obsluzhivaniya.
(Kiev—Service industries)

GLUZMAN, G.L., kand. tekhn. nauk.

Length of service of moving parts of the 37D engine between repairs.
Energomashinostroenie 3 no.10:26-29 0 '57. (MIRA 10:12)
(Diesel engines)

GLUZMAN, G.L., kand. tekhn. nauk

Selecting the finish for the principal wearing parts of diesels.
Energomashinostroenie 4 no. 6:42-44 Jo '58. (MIRA 11:8)
(Diesel engines)

GLUZMAN, G.L., kand.tekhn.nauk

Microstructural changes in the surface layers of materials
subject to friction in the main parts of diesel engines.

Energomashinostroenie 7 no.5:34-35 My '61. (MIRA 14:8)

(Diesel engines)

(Metallography)

S/114/62/000/012/002/007
E194/E135

AUTHORS: Gluzman, G.L., Candidate of Technical Sciences, and
Purgin, B.A., Engineer

TITLE: Assessing the reliability of power sets

PERIODICAL: Energomashinostroyeniye, no.12, 1962, 17-20

TEXT: As power plant becomes more complicated and more highly stressed a need is felt for quantitative assessment of reliability by means of the theory of probability. The following criteria are studied:

1) "the mean time of continuous operation";

$$T_{av} = \frac{\sum_{i=1}^N t_i}{N} \quad (1)$$

where t_i is the operating time of one particular item; N is the number of items of the particular type. This is a simple and revealing index which in effect compares the performance with that of similar plant. Its main disadvantage is that being a

Card 1/3

Assessing the reliability of ...

S/114/62/000/012/002/007
E194/E135

correctly at the start and end of the time interval. This is a convenient characteristic of reliability for power equipment as it demonstrates changes of reliability with time and is easily determined experimentally. It can also be used to determine other criteria of reliability including the mean duration of repair work and the ratio of standstill time to running time. Worked examples are given of the use of these criteria in studying the performance of a diesel engine. There is a particular need for extensive service performance data, but once this is available it becomes possible to set up specific requirements in respect of the reliability of power equipment expressed in numerical terms. There are 2 figures and 1 table.

Card 3/3

GLUZMAN, G.L., kand. tekhn. nauk; BUKIN, P. Ye., inzh.-kapitan 2-go ranga,
kand. tekhn. nauk

Evaluation of the serviceability of power units of surface
ships. Mor. sbor. 49 no. 12:68-71 D ' 65 (MIRA 19:1)

L 29720-66 EWT(1) TG

ACC NR: AP6015406

SOURCE CODE: UR/0375/65/000/012/0068/0071

AUTHOR: Gluzman, G. L. (Candidate of technical sciences); Bukin, P. Ye. (Candidate of technical sciences; Engineer; Commander) ⁴⁰_{E.}

ORG: none

TITLE: Evaluating the operational ²⁵reliability of power stations on surface craft

SOURCE: Morskoy sbornik, no. 12, 1965, 68-71

TOPIC TAGS: statistic analysis, power plant, reliability theory, *marine engineering*

ABSTRACT: The methods of statistical analysis are used for determining the operational reliability of shipboard power stations. The probability of dependable operation of the individual mechanisms is taken as the principal criterion for reliability. This criterion should be given by designers and implemented by industry. Reliability of the power installations is evaluated from the probability for maintaining 100% power as well as at least 75%, 50% and 25% of the rated power and finally the probability for total power loss. These criteria may be used for determining the reliability of the power stations in normal operating conditions as well as in emergency situations. An example is given showing evaluation of the reliability of a turbine boiler installation. Graphs are given which may be used to determine the probability of dependable operation of a power installation when the reliability of the individual units in the

Card 1/2

L 29720-66

ACC NR: AP6015406

0.
installation decreases due to wear after protracted use. It is shown that the reliability of dependable operation depends on the working conditions of the installation. Therefore, these conditions should be strictly defined before a ship leaves port. Formulas are given which may be used to account for the skill of servicing personnel as well as for the average repair time and breakdown frequency. Orig. art. has: 2 figures, 7 formulas.

DATE SUBM: NONE

SUB CODE: 14/ 7 ORIG REF: 006

Card 2/2 C.C.

KOLBERT, G. R., DAVIDSON, G. I.

Hides and Skins

Fermentative and thermal control in lining hides. Leg. proc., No. 1, 1952.

9. Monthly List of Russian Accessions, Library of Congress, March 1958, Uncl.
2

GLUZMAN, G.M., inzhener.

Drying leather glued on glass. Leg.prom.15 no.1:40-42 Ja '55.
(Dyes and dyeing--Leather) (MIRA 8:3)

GLUZMAN, G.M.; GRIGORIADI, M.T.
ZAYONCHKOVSKIY, A.D.; YABKO, Ya.M.; MIKHAYLOV, N.A.; PEKTIISTC', V.K.;
SHMERLING, B.M.; BERNSHTEYN, M.Kh.; GUS'KOV, F.G.; PARAMONOV, V.G.;

Polyamide treatment of imitation kidskin and flesh layer splits.
Leg.prom. 16 no.10:22-26 0 '56. (MIRA 10:12)
(Hides and skins) (Amides)

GLUZMAN, G. M.

27
 Chrome leather. G. M. Gluzman, N. D. Chukhina, V. A. Safonova, N. N. Gurevich, and N. N. Zhuravina. U.S.S.R. 106,153, June 26, 1957. The tanning of chrome leather, such as calfskin, harnessed calf leather, and half-skin is carried out in 2 stages, the 1st lasting half the time of the 2nd. The tanning is done before the 2nd stage of tanning. The drying is done at 35-40°C, and the stretching at a moisture content of 20-25%. For drying, the skins are placed to sheets with an adhesive of sulfonated fish oil and starch or a decolourant of dioxane and caustic, to which is added a synthetic resin (e.g., polyvinyl acetate) or an acrylic resin.

4000
 20000

MT

G. UMAN, G.M.; GRIGORIADI, M.D.

Effect of syntan treatment on drying and finishing glazed chrome
leather. Leg.prom. 17 no.6:26-27 Jo '57. (MIRA 10:8)
(Tanning materials) (Leather)

G. I. UZMAN, G. M.

KOP'YEV, A. I. [deceased]; ZAYONCHKOVSKIY, A. D.; YABKO, Ya. M.; PARINI, V. I.;
PARAMONOV, V. G.; GLUZMAN, G. M.; ORIGORIADI, M. G.

Increasing water repellency in leather by means of a velon-type
compound. Leg.prom. 17 no.7:23-25 J1 '57. (MLRA 10:9)
(Leather Industry)

GLUZMAN, G.M., inzh.

Effect of the surface of various materials and of the method
of gluing in drying on the quality of chrome leather. Kozh.-
obuv. prom. 4 no.7:24-26 J1 '62. (MIRA 17:1)

GLUZMAN, G.M.

Use of various adhesives for chrome leather drying by
adhesion. Kozh.-obuv.prom. 4 no.9:27-29 S '62. (MIRA 15:9)
(Leather--Drying)
(Adhesives)

GLUZMAN, I.A., inzh.

About performance of the soot-blowing devices of the "Ilmarine"
Works. Teploenergetika 4 no.12:91-92 D '57. (MLRA 10:11)
(Boilers)

L 04251-67 EWT(d), LWT(m)/EWP(E)/T DJ

ACC NR: AP6005389

(N)

SOURCE CODE: UR/0413/66/000/001/0110/0110

AUTHORS: Kreysler, A. A.; Gorodetskiy, K. I.; Glusman, I. A.

23
22

ORG: none

B

TITLE: An axial piston pump. ²³ Class 59, No. 177774

SOURCE: Izobreteniya, promyshlennyye obraztsy, tovarnyye znaki, no. 1, 1966, 140

TOPIC TAGS: axial pump, fluid pump

ABSTRACT: This Author Certificate presents an axial piston pump with a support on the intake and with a rotating cylinder block. The pump includes connecting rods with double-sided joints. One of the joints is connected with the piston and the other with the socket (see Fig. 1). The socket is mounted on one of the axial holes of the drive shaft flange and transmits the pressure force of the liquid being pumped through the hydrostatic bearing to the pump casing. The design reduces the leakage and increases the pump efficiency. The axial holes in the drive shaft flange run clear through, and each socket mounted in the hole contacts its flat face directly with the casing or is connected with a fixed part of the casing. Each socket has a recess in its flat face and is connected by axial channels to the connecting rod and the piston and to the proper operating chamber. This arrangement provides the

Card 1/2

UDC: 621.659

ACC NR: AP6005389




Fig. 1. 1 - cylinder block; 2 - connecting rods; 3 - pistons; 4 - socket; 5 - drive shaft; 6 - recess in the socket

individual hydrostatic bearing of each piston and the correspondence between the back pressure in the bearing and the pressure in the operating chamber. Orig. art. has: 1 figure.

SUB CODE: 13/ SUBM DATE: 02Jun62

Card 2/2 Ev

GLUZMAN, I.I. (Vinnitsa)

Selection of numerical data for composing problems solvable
according to the Pythagorean theorem. Mat. v shkole no. 3:62
My-Je '61. (MIRA 14:5)
(Pythagorean proposition)

GLUZMAN, I.S., kandidat tekhnicheskikh nauk, redaktor; KALININ, V.K.,
inzhener, redaktor; KHITROV, P.A., tekhnicheskii redaktor

[Signaling, central control and block systems of foreign railroads;
a collection of articles] Ustroistva STsB zarubezhnykh zheleznnykh
dorog; sbornik statei. Moskva, Gos. transp. zhel-dor. izd-vo, 1956.
131 p. (MLRA 9:10)

(Railroads--Signaling)

OLUZMAN, I.S., kandidat tekhnicheskikh nauk.

Rail circuits with electron tubes used by French railroads. Zhel.
dor.transp. 37 no.7:88-89 J1 '56. (MLBA 9:8)
(France--Electric locomotives)

GLUZMAN, I.S., kand.tekhn.nauk, red.; CHUKMENNIV, N.M., inzh., red.;
BOBROVA, Ye.N., tekhn.red.

[New methods in signal, central control, and blocking systems for
railroads in other countries; a collection of articles] Novaya
tekhnika SSSR na zarubezhnykh zheleznykh dorogakh; sbornik statei.
Moskva, Gos. transp.zhel-dor. izd-vo, 1957. 129 p. (MIRA 11:5)
(Railroads)

GLUZMAN, I.S.; KARNYUSHIN, L.V., dotsent.

System of pneumatic transportation of steel specimens in metallurgical plants. Zav. lab. 23 no.4:502-503 '57. (MLBA 10:6)

1. Master Beresnyakovskogo montashnogo upravleniya tresta "Uralslektromontash" (for Gluzman). 2. Zaveduyushchiy kafedroy elektrifikatsii promyshlennykh predpiyatii L'vovskogo politekhnicheskogo instituta (for Karnyushin).
(Pneumatic-tube transportation)

GIUZMAN, Il'ya Samoylovich, kand.tekhn.nauk; MOSHENTSEVA, I.I., red.;
~~MURASHOVA, N.K., kand.tekhn.red.~~

[English-Russian dictionary on railroad signaling and communication] Anglo-russkii slovar' po zheleznodorozhnoi avtomatike, telemekhanike i svyazi. Moskva, Gos. izd-vo fiziko-matem. lit-ry.
1958. 427 p. (MIRA 12:2)

(Railroad engineering--Dictionaries)
(English language--Dictionaries--Russian)
(Railroads--Signaling)

GLUZMAN, I.S., kand.tekhn.nauk

Small control devices for centralized traffic control. Avtom.,
telem.1 sviaz 2 no.4:45-47 Ap '58. (MIRA 12:12)
(Railroads--Signaling--Centralized traffic control)

GLUZMAN, I.S., kand. tekhn. nauk

Electronic track circuits. Avtom. telemek. i svyaz' 2 no.12:42-43
D '58. (MIRA 11:12)

(France--Railroads)

GLUZMAN, I.S., kand.tekhn.nauk

Building of signaling systems in the U.S. Avtom., telen.1
sviaz 3 no.9:47 S '59. (MIRA 13:2)
(United States--Railroads--Signaling)

GLUZMAN, I.S., kand.tekhn.nauk; MARENKOVA, G.I., inzh., red.;
BOBROVA, Ye.N., tekhn.red.

[New developments in automation and remote control on foreign
railroads; translated articles] Novoe v avtomatike i telemekhanike
na zarubezhnykh zheleznnykh dorogakh; perevod statei. Moskva,
Vses.izdatel'sko-poligr.ob"edinenie M-va putei soobshchenia, 1960.
165 p. (MIRA 13:11)

(Railroads--Electronic equipment)
(Remote control)

(Automatic control)

GLUZMAN, I.S.

ALATORTSEV, S.A., prof., doktor tekhn.nauk; ANDREYEV, A.V., kand.tekhn.nauk; ANCHAROV, I.L., inzh.; BALINSKIY, S.I., inzh.; BELOUSOV, V.G., inzh.; VINNITSKIY, K.Ye., kand.tekhn.nauk; VLASOV, V.M., inzh.; VORONTSOV, N.P., kand.tekhn.nauk; GIPSMAN, M.K., inzh.; GLUZMAN, I.S., kand.tekhn.nauk; GUR'YEV, S.V., kand.tekhn.nauk [deceased]; DEMIN, A.M., kand.tekhn.nauk; YEGORNOV, G.P., kand.tekhn.nauk; YEFIMOV, I.P., inzh.; ZHUKOV, L.I., kand.tekhn.nauk; ZEL'TSER, N.M., inzh.; KOSACHEV, M.N., kand.tekhn.nauk; KOTOV, A.F., inzh.; KUDINOV, G.P., inzh.; LAPOVENKO, N.A., kand.tekhn.nauk; MAZURCK, S.F., inzh.; MEL'NIKOV, N.V.; MUDRIK, N.G., inzh.; NIKONOV, G.P., kand.tekhn.nauk; ORLOV, Ye.I., inzh.; POTAPOV, M.G., kand.tekhn.nauk; PRISEDSKIY, G.V., inzh.; RZHEVSKIY, V.V., prof., doktor tekhn.nauk; RYAKHIN, V.A., kand.tekhn.nauk; SIMKIN, B.A., kand.tekhn.nauk; SITNIKOV, I.Ye., inzh.; SOROKIN, V.I., inzh.; SPASYUK, V.N., kand.tekhn.nauk; STAKHEVICH, Ye.B., inzh.; SUSHCHENKO, A.A., inzh.; TYUTIN, I.F., inzh.; TYMOVSKIY, L.G., inzh.; FISENKO, G.L., kand.tekhn.nauk; FURMANOV, B.M., inzh.; SHATAYEV, M.G., inzh.; SHESHKO, Ye.F., prof., doktor tekhn.nauk; TERPIGOREV, A.M., glavnyy red. [deceased];

(Continued on next card)

ALATORTSEV, S.A.---(continued) Card 2.

KIT, I.K., zamestitel' glavnogo red.; SHESHKO, Ye.F., zamestitel' otv.red.; BUGOSLAVSKIY, Yu.K., red.; BYKHOVSKAYA, S.N., red.; DIONIS'YEV, A.I., kand.tekhn.nauk, red.; KOZIN, Yu.V., red.; SOKOLOVSKIY, M.M., red.; YASTREDOV, A.I., red.; DEMIDYUK, G.P., kand.tekhn.nauk, red.; KRIVSKIY, M.N., kand.tekhn.nauk, red.; LYUBIMOV, B.N., inzh., red.; MOLOKANOV, P.L., inzh., red.; REISH, A.K., inzh., red.; RODIONOV, L.Ye., kand.tekhn.nauk, red.; SLAVUTSKIY, S.O., inzh., red.; TRAKHMAN, A.I., inzh., red.; TRYMOVSKIY, L.G., inzh., red.; FIDELEV, A.S., doktor tekhn.nauk, red.; SHUKHOV, A.N., kand.tekhn.nauk, red.; TER-IZRAEL'YAN, T.G., red. izd-va; PROZOROVSKAYA, V.L., tekhn.red.; KONDRAT'YEVA, M.A., tekhn.red.

(Continued on next card)

ALATORTSEV, S.A.---(continued) Card 3.

[Mining; an encyclopedic dictionary] Gornoe delo; entsiklopedicheskii spravochnik. Glav.red.A.M.Terpigorev. Chleny glav.red.A.I.Baranov i dr. Moskva, Gos.nauchno-tekhn.izd-vo lit-ry po gornomu delu. Vol.10. [Mining coal deposits by the open-cut method] Razrabotka ugol'nykh mestorozhdenii otkrytym sposobom. Redkollegia toma; N.V.Mel'nikov i dr. 1960. 625 p.

(MIRA 13:2)

1. Chlen-korrespondent AN SSSR (for Mel'nikov).
(Coal mines and mining) (Strip mining)

GIUZMAN, I.S., dots., kand.tekhn.nauk

Signaling devices on French railroads. Avtom., telem. i sviaz'
4 no.7:44-48 JI '60.. (MIRA 13:7)
(~~France--Railroads--~~Signaling)

LUPAL, Nikolay Vasil'yevich; BOSIN, Matvey Itskovich; PEREBOROV,
Aleksandr Sergeyevich; SMIRNOVA, Appolinariya Vasil'yevna;
Mylar, Aleksandr Aleksandrovich; TSUKANOV, T.T., kand.
tekhn.nauk, retsensént; SHUPOV, V.I., kand.tekhn.nauk,
retsensént; GLUZMAN, I.S., kand.tekhn.nauk, red.;
USHENKO, L.A., tekhn.red.

[Theoretical principles of automatic and remote control]
Teoreticheskie osnovy avtomatiki i telemekhaniki. By N.V.
Lupal i dr. Moskva, Vses.isdatel'sko-poligr.ob"edinenie
M-va putei soobshchenia, 1961. 414 p.

(MIRA 14:12).

(Automatic control)

(Remote control)

GLUZMAN, I.S., kand.tekhn.nauk

Session of the signaling section of the American Railway Association.
Avtom., telem. i sviaz' 5 no.5:46-47 My '61. (MIRA 14:6)
(Chicago--Congresses)
(United States--Railroads--Signaling)
(Railroads--Congresses)

KOTLYARENKO, N.V., kand. tekhn. nauk; MANOSHIN, N.K., inzh.;
TSETSTURA, I.A., inzh.; LEONOV, A.A., inzh., retsenzent;
~~GLUZMAN, S.S.~~, kand. tekhn. nauk, red.; VOROTNIKOVA,
L.F., tekhn. red.

[Track circuits] Rel'sovye tsepi. Moskva, Transzheldorizdat,
1963. 142 p. (MIRA 16:10)
(Railroads--Signaling)(Railroads--Electric equipment)

GLUZMAN, I.S., kand. tekhn. nauk

Automatic car checking on railroads in Great Britain.
Avtom., telem. i svyaz' 7 no.6:46-47. Ie '63.

(MIRA 17:3)

GLUZMAN, I.S., kand. tekhn. nauk

Single-track automatic block system with two-line wires. Avtom.,
telem. i sviaz' 7 no.11:44-47 N '63. (MIRA 16:12)

GLUZMAN, I.S., kand. tekhn. nauk

Crossing signaling system with timed action. Avtom. telem.
i sviaz' 8 no. 3:46-48 Mr '64. (MIRA 17:5)

GLUZMAN, I.S., kand. tekhn. nauk

Use of cybernetics in railroad transport. Avtom. izm.

1 sviaz' 8 no.6:17-19 Je '64.

(MIRA 17:0)

PEREBOROV, Aleksandr Sergeyevich, kand. tekhn. nauk; SEMKO,
Vikto Nikolayevich, kand. tekhn. nauk; RATNIKOV,
Vladimir Dmitriyevich, inzh.; KARVATSKIY, S.B., kand.
tekhn. nauk, retsenzent; GLUZMAN, I.S., red.

[Remote control of switches and signals] Teleupravlenie
strelkami i signalami. Moskva, Transport, 1965. 383 p.
(MIRA 18:8)

GAL'PERIN, Yu.B., podpolkovnik med. sluzhby, GLUTMAN, I.S., mayor med.sluzhby

Case of prolonged retention of a contrast medium in the nasolacrimal canal. Oft.zhur. 13 no.5:306-307 '58 (MIRA 11:10)

1. Iz Laringo-oto-rino kafedry im. prof. V.I. Voyacheka i kafedry oftal'mologii (nach. - prof. B.L. Polyak) Voenno-meditsinskoy ordena Lenina akademii im. S.M. Kirova.
(LACRIMAL ORGANS--RADIOGRAPHY)

[illegible]

PROCESS AND PROPERTY INDEX																									
LIST AND NO. GROUPS													LIST AND NO. GROUPS												
<p>Purifying phenanthrene. L. D. Gelfman and A. M. Krasovskii. Russ. 43,446, 1945. Crude phenanthrene is heated to 101-30° in the presence of strong H₂SO₄ (not more than 30% of H₂SO₄ on the wt. of phenanthrene).</p>																									
<p>ASM-SLA METALLURGICAL LITERATURE CLASSIFICATION</p>																									

1ST AND 2ND SHEETS										PROCESSES AND PROPERTIES MOVED									
BC										B-II-1									
<p>1. Preparation of high-grade phosphorus, 99.5% pure, and HCC (hydrocarbons) (Franklin, Cal. 1957, p. 200-201). The phosphorus was obtained from a mixture of waste materials with "residue" in which the fraction of 1.5-2.0-3.0% passed at 200-300 mesh, the residue (hydrocarbons) 20-30% of phosphorus (1), heated at 200-300° for 2-3 hr. with 50% of waste, 100% and the hydrocarbons (2) collected at 200, washed with hot H₂O, and distilled, with the fraction of 1.5-2.0-3.0% consists of 20-30% (1), 10-20% (2) is prepared by separating the phosphorus, hydrocarbons from the residue to H₂O, H₂.</p>																			
ASD-11A METALLURGICAL LITERATURE CLASSIFICATION										48000 50000 48000 50000 48000 50000									
48000 50000 48000 50000 48000 50000										48000 50000 48000 50000 48000 50000									

21

Methods of working up coal-tar pitch. L. D. Ghaman, S. M. Grigor'ev and V. S. Khadzhinov. *Coke and Chem.* (U. S. S. R.) 7, No. 11, 50-5 (1957); *Chem. Zentr.* 1958, II, 3492. - A general review of the possibilities of recovery and use of compds. occurring in coal-tar pitch.

M. G. Moser

1958

1957

1956

1955

1954

1953

1952

1951

1950

1949

1948

1947

1946

1945

1944

1943

1942

1941

1940

1939

1938

1937

1936

1935

1934

1933

1932

1931

1930

1929

1928

1927

1926

1925

1924

1923

1922

1921

1920

1919

1918

1917

1916

1915

1914

1913

1912

1911

1910

1909

1908

1907

1906

1905

1904

1903

1902

1901

1900

1899

1898

1897

1896

1895

1894

1893

1892

1891

1890

1889

1888

1887

1886

1885

1884

1883

1882

1881

1880

1879

1878

1877

1876

1875

1874

1873

1872

1871

1870

1869

1868

1867

1866

1865

1864

1863

1862

1861

1860

1859

1858

1857

1856

1855

1854

1853

1852

1851

1850

1849

1848

1847

1846

1845

1844

1843

1842

1841

1840

1839

1838

1837

1836

1835

1834

1833

1832

1831

1830

1829

1828

1827

1826

1825

1824

1823

1822

1821

1820

1819

1818

1817

1816

1815

1814

1813

1812

1811

1810

1809

1808

1807

1806

1805

1804

1803

1802

1801

1800

1799

1798

1797

1796

1795

1794

1793

1792

1791

1790

1789

1788

1787

1786

1785

1784

1783

1782

1781

1780

1779

1778

1777

1776

1775

1774

1773

1772

1771

1770

1769

1768

1767

1766

1765

1764

1763

1762

1761

1760

1759

1758

1757

1756

1755

1754

1753

1752

1751

1750

1749

1748

1747

1746

1745

1744

1743

1742

1741

1740

1739

1738

1737

1736

1735

1734

1733

1732

1731

1730

1729

1728

1727

1726

1725

1724

1723

1722

1721

1720

1719

1718

1717

1716

1715

1714

1713

1712

1711

1710

1709

1708

1707

1706

1705

1704

1703

1702

1701

1700

1699

1698

1697

1696

1695

1694

1693

1692

1691

1690

1689

1688

1687

1686

1685

1684

1683

1682

1681

1680

1679

1678

1677

1676

1675

1674

1673

1672

1671

1670

1669

1668

1667

1666

1665

1664

1663

1662

1661

1660

1659

1658

1657

1656

1655

1654

1653

1652

1651

1650

1649

1648

1647

1646

1645

1644

1643

1642

1641

1640

1639

1638

1637

1636

1635

1634

1633

1632

1631

1630

1629

1628

1627

1626

1625

1624

1623

1622

1621

1620

1619

1618

1617

1616

1615

1614

1613

1612

1611

1610

1609

1608

1607

1606

1605

1604

1603

1602

1601

1600

1599

1598

1597

1596

1595

1594

1593

1592

1591

1590

1589

1588

1587

1586

1585

1584

1583

1582

1581

1580

1579

1578

1577

1576

1575

1574

1573

1572

1571

1570

1569

1568

1567

1566

1565

1564

1563

1562

1561

1560

1559

1558

1557

1556

1555

1554

1553

1552

1551

1550

1549

1548

1547

1546

1545

1544

1543

1542

1541

1540

1539

1538

1537

1536

1535

1534

1533

1532

1531

1530

1529

1528

1527

1526

1525

1524

1523

1522

1521

1520

151

[illegible]

Separation of highly concentrated *m*-cresol from its mixture with *p*-cresol. L. H. Glusman, V. A. Ivanushkina and K. Bel'jamin. *Org. Chem.* 1954, 1, 1583, 3, 682-2 (1954). In the modified method of Comte (U. S. pat. 1,980,364; C. A. 20, 1821), involving the use of NaOAc, a yield of 68% of 98-96% pure *m*-cresol is obtained from a crude product, contg. 42% *m*- and 58% *p*-cresol, by the use of CaO, instead of petroleum naphtha as a solvent and direct distn., with stirring, preferably at reduced pressure, of the solid NaOAc-*m*-cresol soln. product. The anhyd. NaOAc is recovered and is used 3 times in the process before the dehydration. The best times in the process is best with 10% of anhyd. NaOAc of *m*-cresol proceeds best with 10% of anhyd. NaOAc at 20-6° instead of 45°. The addn. product can also be decompd. by adding 0.7-1 part of PhMe, stirring the mixt. at 60-80° for 15-30 min., filtering at 25-40° and distg. off the *m*-cresol from the filtrate as usual.

Chas. Blanc

Chas. Blane

ASU-5LA METALLURGICAL LITERATURE CLASSIFICATION

13

Production of high melting comonomer resin at the Ruffchenkov factory. M. A. Stepanenko and L. D. Ghrman. *Khimiya* 1938, No. 7, 103. The ethyl styrene fraction, b. 160-180°, is heated with vigorous stirring at 60° with 1.5 vols. of 92-5% H₂SO₄. The product is thoroughly washed with H₂O, aq. NaOH, and H₂O, and unpolymerized constituents are removed by steam-distn. The residual resin, subjected to fractional distn. in vacuo, yields a product m. 85-98°. H. C. P. A.

ASAC 54.4 METALLURGICAL LITERATURE CLASSIFICATION

Preparation of gasometer oil. S. M. Gogorov, E. D. Gluzman and A. S. Nepomnashchaya. *Fuel and Chem. (U. S. S. R.)* 1938, No. 10, 35-9. Anthracene oil is fractionated, the fractions are cooled, allowed to crystallize at room temp. and filtered, and the η of the filtrate is adjusted by addn. of cylinder oil. For winter use the oil is dild. with PbCl_2 or CaCl_2 . The superiority of this over the usual freezing-out method lies in recovery of valuable cryst. by-products. R. C. P. A.

ASB-11A METALLURGICAL LITERATURE CLASSIFICATION

CU

21

Production of fluorene, acenaphthene, diphenylene oxide and o-diphenol from coal tar, and their purification
S. M. Grigor'ev, L. K. Gubanov, V. A. Ivanushkina and
D. I. Kraslavskaya. *Chem. Ind. (U.S.S.R.)*, No. 11, 347 (1960); *Chem. & Industry* 44, 43 (1960)
By fusing the coal-tar fractions boiling between 278° and 300° with solid KOH pure acenaphthene, fluorene and o-diphenol can be sep'd. The reaction must be carried out at the b. p. of the fraction treated. On the other hand, by rectification of the suitable fractions, followed by crystallization and purification with H₂SO₄, fluorene and diphenylene oxide can be ext'd.
A. Papineau-Couture

ASAC 11-1 DETAIL JOURNAL LITERATURE CLASSIFICATION

21

Ed

Determination of fluorene alone and in coal-tar fractions. L. D. Gluzman and G. M. Popova. *Trudy Khim. i. Nakh. Tselokh. Uglekhim. Inst.* 1960, No. 10, 175-87; *Khim. Referat. Zhur.* 6, No. 9, 87 (1941). A no. of methods for detg. fluorene were examd. Nitration to 2-nitrofluorene in AcOH soln. gave the best results. The conditions for nitrating were studied and the yield of the product (m. 152-3°) was increased to 85.5-91.0%. The nitro derivs. of phenanthrene, acenaphthene and diphenylene oxide were sol. more in AcOH under the conditions described than was 2-nitrofluorene. Dissolve 2 g. of sample and 1 g. of fluorene in 30-42 cc. of glacial AcOH, cool, add slowly 6.6 cc. of HNO₃ (d. 1.38-1.40) at 50-60°, increase the temp. slowly to 80-85°, nitrate for 30 min., add 25 cc. of AcOH, cool, filter out the 2-nitrofluorene, wash with 5cc. of AcOH and dry at 100-20°. W. R. H.

ASB-518 DETAILING LITERATURE CLASSIFICATION

10000 00000

10000 00000

10000 00000

21

The extraction of pyridine bases from various products of the carbonization industry. L. D. Gluzman and S. M. Grigor'ev. *Coke and Chem.* (U. S. S. R.) 11: No. 2, 39-35 (1961); *Chem. Zvest.* 1963, I, 1128-9.—A description is given of processes and equipment used for isolating pyridine bases (I) from coal tar, crude benzene, coke-oven gas, ammonia liquor, $(\text{NH}_4)_2\text{SO}_4$, and the basic liquors of saturators. After $(\text{NH}_4)_2\text{SO}_4$ removal by centrifuging, the saturator liquor is neutralized by vapor from the NH_3 still and then strain-distilled at 100–105°. A yield of 75–80% of I with respect to the content in the liquor is obtained in the first 1–6% of condensate. The distillate contg. I can be run into H_2O , from which I is salted out by using solid $(\text{NH}_4)_2\text{SO}_4$. The upper layer contains 70% of I. The process can be made continuous, in which method NH_3 and steam are blown through the saturator liquor at 60–80°.

Glenn C. Smith

11

21

31

41

51

61

71

81

91

101

111

121

131

141

151

161

171

181

191

201

211

221

231

241

251

261

271

281

291

301

311

321

331

341

351

361

371

381

391

401

411

421

431

441

451

461

471

481

491

501

511

521

531

541

551

561

571

581

591

601

611

621

631

641

651

661

671

681

691

701

711

721

731

741

751

761

771

781

791

801

811

821

831

841

851

861

871

881

891

901

911

921

931

941

951

961

971

981

991

1001

1011

1021

1031

1041

1051

1061

1071

1081

1091

1101

1111

1121

1131

1141

1151

1161

1171

1181

1191

1201

1211

1221

1231

1241

1251

1261

1271

1281

1291

1301

1311

1321

1331

1341

1351

1361

1371

1381

1391

1401

1411

1421

1431

1441

1451

1461

1471

1481

1491

1501

1511

1521

1531

1541

1551

1561

1571

1581

1591

1601

1611

1621

1631

1641

1651

1661

1671

1681

1691

1701

1711

1721

1731

1741

1751

1761

1771

1781

1791

1801

1811

1821

1831

1841

1851

1861

1871

1881

1891

1901

1911

1921

1931

1941

1951

1961

1971

1981

1991

2001

2011

2021

2031

2041

2051

2061

2071

2081

2091

2101

2111

2121

2131

2141

2151

2161

2171

2181

2191

2201

2211

2221

2231

2241

2251

2261

2271

2281

2291

2301

2311

2321

2331

2341

2351

2361

2371

2381

2391

2401

2411

2421

2431

2441

2451

2461

2471

2481

2491

2501

2511

2521

2531

2541

2551

2561

2571

2581

2591

2601

2611

2621

2631

2641

2651

2661

2671

2681

2691

2701

2711

2721

2731

2741

2751

2761

2771

2781

2791

2801

2811

2821

2831

2841

2851

2861

2871

2881

2891

2901

2911

2921

2931

2941

2951

2961

2971

2981

2991

3001

3011

3021

3031

3041

3051

3061

3071

3081

3091

3101

3111

3121

3131

3141

3151

3161

3171

3181

3191

3201

3211

3221

3231

3241

3251

3261

3271

3281

3291

3301

3311

3321

3331

3341

3351

3361

3371

3381

3391

3401

3411

3421

3431

3441

3451

3461

3471

3481

3491

3501

3511

3521

3531

3541

3551

3561

3571

3581

3591

3601

3611

3621

3631

3641

3651

3661

3671

3681

3691

3701

3711

3721

3731

3741

3751

3761

3771

3781

3791

3801

3811

3821

3831

3841

3851

3861

3871

3881

3891

3901

3911

3921

3931

3941

3951

3961

3971

3981

3991

4001

4011

4021

4031

4041

4051

4061

4071

4081

4091

4101

4111

4121

4131

4141

4151

4161

4171

4181

4191

4201

4211

4221

4231

4241

4251

4261

4271

4281

4291

4301

4311

4321

4331

4341

4351

4361

4371

4381

4391

4401

4411

4421

4431

4441

4451

4461

4471

4481

4491

4501

4511

4521

4531

4541

4551

4561

4571

4581

4591

4601

4611

4621

4631

4641

4651

4661

4671

25

Control Kokushnitskhesago Proizvodstva. (Control in the Coke-Chemical Industry.) Ed. A. I. D. Glazman and I. I. Edel'man. 455 pages. 1946. State Scientific-Technical Publishing House for Ferrous and Nonferrous Metallurgical Literature, Moscow, USSR.

Consists of a laboratory manual and handbook for personnel of above plants. Includes comparative experimental evaluation of the various methods. Numerous tables, diagrams, and graphs. 32 ref.

ASB-31.4 METALLURGICAL LITERATURE CLASSIFICATION

21

Ca

Ushakov, L. D., and Kozlov, I. I.: Methods of Control in the Coking Industry. 2nd ed. (in Russian.) Moscow: Metallurgizdat, 1947. 456 pp. Reviewed in Chem. Eng. 55, No. 1, 282(1948).

ASTM-51A METALLURGICAL LITERATURE CLASSIFICATION

METALLURGICAL LITERATURE CLASSIFICATION																									
CLASSIFICATION													SUBJECT												
CLASSIFICATION													SUBJECT												
<p>2889. METHODS OF CONTROL IN THE COOKING INDUSTRY. (KONTROL' KOKSOKHIMICHESKOGO PROIZVODSTVA). Glusman, L. D. and Edel'man, I. I. (Moscow: Metallurgizdat, 456pp.; Chem. Engng. Jan. 1948, Vol. 55, No. 1. 292-293). The book was written for chemists working in coking plants in the U.S.S.R. and its chapters on analysis and control refer to several methods originally developed in the U.S.S.R., as well as foreign methods, a number of them German, adapted or modified by the Russians. The first part of the book concerns control of coal concentration, as aying of coal and methods of control of the coking process; the second part is devoted to separation and processing of gas and tar components.</p>																									

GLUZHANSKY, L. D.

✓ 2158. Rapid determination of nitrogen in un-
refined anthracene and its refining products. L. D.
Gluzhansky, R. I. Melamed and D. S. Khinkhishvili
Inst. for the Chemistry of Coal, Zverov. Lab.,
1955, 21 (12), 1433-1435. — The anthracene material
(0.1 g) in a 50 ml Kjeldahl flask is heated to com-
plete dissolution with 10 ml of conc. H_2SO_4 (about
3 to 5 min.) and then small portions of finely divided
 $K_2Cr_2O_7$ (2-4 g in all) are added with stirring during
the continued heating of the flask (about 5 to 7 min.).
The heating is continued further (5 to 7 min.) until
a bright-green paste is obtained. The temperature
throughout should be 250° to 260° C. After being
cooled, the contents are transferred to a distillation
flask and the NH_3 is determined by the usual
method. The time taken is 15 to 20 min. for
decomposition and 30 min. for distillation.

G. S. Smith

PM [signature]

LITVINENKO, M.S.; NOSALEVICH, I.M.; GLUZMAN, L.D.; GIMMEL'SHTEYN, T.Ye.;
KOLTUN, R.M.

Tasks of the byproduct coking industry in augmenting the number of
coke-oven by-products. Koks i khim. no.3:41-45 '56. (MLRA 9:8)

1. Ukrainskiy/uglekhimicheskiy institut (for Litvinenko, Nosalevich,
Gluzman); 2. Giprokoks (for Gimmel'shteyn); 3. Khar'kovskiy
koksokhimicheskiy zavod.
(Coke industry)

GLUZMAN, L.D.; TSIN, R.M.

Determination of chlorides and rhodanides in coal tar and its
fractions. Zav.lab. 22 no.1:45-46 '56. (MLBA 9:5)

1. Ukrainskiy nauchno-issledovatel'skiy uglekhimicheskiy institut.
(Chlorides--Analysis) (Thiocyanates--Analysis) (Coal tar)

GLUZMAN, Lyubov' Davydovna; EDEL'MAN, Ita Iosifovna; FOSS, B.I., otvetstven-
nyy redaktor; SIBYAVSKAYA, Ye.K., redaktor izdatel'stva; LEBESLAV,
S.S., redaktor izdatel'stva; ANDREYEV, S.P., tekhnicheskii redaktor

[Laboratory control of the by-product coke industry] Laboratornyi
kontrol' koksokhimicheskogo proizvodstva. Izd. 4-oe, perer. i dop.
Khar'kov, Gos.nauchno-tekhn.izd-vo lit-ry po cherno i tsvetnoi
metallurgii, 1957. 635 p. (MIRA 10:10)
(Coke industry)

GLUZMAN, L.D.

68-1-14/21

AUTHOR: Gluzman, L.D.

TITLE: Flash Evaporation of Coal Tar. (Odnokratnoye ispareniye kamennougolnoy smoly)

PERIODICAL: Koks i Khimiya, 1957, No.1, pp. 45 - 49 (USSR)

ABSTRACT: Flash evaporation curves (relationship between the temperature of evaporation and the proportion of distillate obtained) for coal tars produced on the Zaporozhskiy and Gorlovskiy Coke Oven Works were determined. The apparatus used was similar to that described in Ref.2. Characteristics of coal tars investigated are given in Table 1 and their flash evaporation curves in Fig.1. The yield of phenols, bases and naphthalene are given in Table 2 and Fig.2. The distribution of fractions of coal tar between the distillate and pitch during flash evaporation at various temperatures (300 - 405 °C) is given in Table 3. Analyses of pitch produced during flash evaporation of coal tar from the Zaporozhskiy Works (for 1954) is given in Table 4. The dependence of softening temperature of pitch on the percentage of distillate and the temperature of flash evaporation is shown in Fig.3, and their content of toluene insoluble and free carbon in Fig.4. The dependence between the softening temperature of pitch (y) and the temperature of flash evaporation (x) can be expressed by an equation

Card 1/2

Flash Evaporation of Coal Tar.

68-1-14/21

$y = 0.835x - 250$. x and y in $^{\circ}\text{C}$). The equation holds within flash evaporating temperatures $300 - 420^{\circ}\text{C}$. The dependence of the percent content of toluene insoluble substances in pitch (y) on the flash evaporation temperature (x) can be expressed by an equation $y = 0.715x - 46.5$. The results of the investigation indicated that within the temperature range $300 - 400^{\circ}\text{C}$, the flash evaporation curves for tars from both works practically coincide and are represented by a straight line. An increase in flash evaporation temperature up to 440°C (and generally above 410°C) leads to losses of phenols and does not increase the yield of naphthalene. A complete recovery of technically useful phenols and naphthalene in the distillate takes place at a flash distillation temperature of $380 - 400^{\circ}\text{C}$. With increasing flash evaporation temperature above 380°C , the content of high boiling components in the distillate increases which leads to a deterioration in the quality of anthracene oil. The data obtained confirm the expediency of collection of two anthracene fractions for the production of a good-quality product for preserving railway sleepers and a raw anthracene. There are 4 tables, 5 graphs and 3 Slavic references.

ASSOCIATION: UKhIN

AVAILABLE: Library of Congress

Card 2/2

AUTHOR: Gluzman, L. D.

68-58-4-10/21

TITLE: The Production of High Concentration Anthracene and Carbozole from Raw Anthracene by Recrystallisation from Solvents (Poluchenkiye vysokoprotsentnykh antratsena i karbazola iz syrogo antratsena perekristallizatsiyey iz rastvoriteley)

PERIODICAL: Koks i Khimiya, 1958, Nr 4, pp 35-42 (USSR)

ABSTRACT: On the basis of literature data and previous work on the subject carried out by UKhIN the author proposed a scheme for the beneficiation of raw anthracene with a mixture of pyridine bases and toluene (a diagram is given). The scheme was designed on the basis of the following considerations: a) Raw material - redistilled raw anthracene containing 25-30% of anthracene, 10-15% of carbozole; 95% of the product boils out to 350°C (the temperature corrected). b) Solvent: a mixture of light pyridine bases (mainly pyridine) with toluene in a ratio of 1:1 by weight. Bases should boil out to 200°C. The amount of solvent is calculated as 7.5 - 8 parts per part of carbozole in the raw anthracene. c) The apparatus and the course of

Card 1/2

68-58-4-10/21
The Production of High Concentration Anthracene and Carbazole
from Raw Anthracene by Recrystallisation from Solvents

beneficiation are shown in the diagram.

There are 5 tables, 1 figure and 4 references, all of
which are Soviet.

ASSOCIATION: UKhIN - *Ukrainskiy khimicheskii institut*

1. Anthracenes--Production
2. Carbazoles--Production
3. Anthracenes--Crystallization
4. Carbazoles--Crystallization
5. Organic solvents--Performance

Card 2/2

AUTHOR: Gluzman, L.D. SOV/68-58-2-11/20

TITLE: The Production of Phenanthrene of Various Degrees of Purity (Polucheniye fenantrena razlichnoy stepeni chistoty)

PERIODICAL: Koks i Khimiya, 1959, Nr 2, pp 39 - 43 (USSR)

ABSTRACT: The possibility of production of technically pure phenanthrene (70-85%) from raw anthracene, anthracene oil, mother liquor from beneficiation of raw anthracene by solvents, etc. was demonstrated. A method of producing phenanthrene of any desired degree of purity from technical phenanthrene was developed. The method consists of fusing of the technical product with 20% of solid potassium hydroxide. The fusion takes place in two stages: at 240 - 260 °C carbozol reacts with alkali, then the temperature should be increased to 300 - 335 °C and retained for 3 hours. On this treatment practically all the components of technical phenanthrene are transferred into the alkali layer. After the separation of hydrocarbon and alkali layer, the former is re-distilled in order to separate completely alkali and coking residue. The results of alkali treatment are shown in Table 4. In order to remove anthracene, the re-distilled product is fused for 3-4 hours at 130 - 140 °C with maleic

Card1/2

SOV/68-58-2-11/20

The Production of Phenanthrene of Various Degrees of Purity

anhydride added in a proportion of 110% of the theoretical (calculated on anthracene). Then the product is treated with 15% solution of sodium hydroxide at 100 - 105 °C in order to separate the excess of maleic anhydride. The hydrocarbon separated from alkali solution is redistilled and recrystallised twice from alcohol. The product so obtained is free from anthracene, carbozol and diphenyl-enesulphide and contains above 99% of pure phenanthrene melting at a temperature of about 100 °C. There are 4 tables and 6 references, 3 of which are English, 1 Soviet, 1 German and 1 French.

ASSOCIATION: UKhIN

Card 2/2

S/068/60/000/010/001/001
E071/E435

AUTHORS: Gluzman, L.D., Gilyazetdinov, L.P. and
Molchanov, B.A.

TITLE: On the Utilization of High Boiling Coal Tar Fractions
for the Production of Carbon-Black


PERIODICAL: Koks i khimiya, 1960, No.10, pp.51-54

TEXT: The problem of production of an active carbon black from raw materials derived from the coking by-products and the development of technological and GOST standards for coal tar raw materials for the production of carbon black were investigated. Typical samples of coal-tar oils (creosote absorption oil; a mixture of absorption and anthracene oil; anthracene fraction I; anthracene fraction II; pitch distillate) from the Kadiyevsk and Zaporozhsk Coking Works were taken for the investigation. Physico-chemical characteristics of these oils and, for comparison, of some petroleum oils are given in Table 1. Group-structural analysis of the petroleum and coal tar oils was calculated by the methods given in earlier works (Ref.3 and 4). The product of the total number of benzene rings in the molecule and the content of carbon in the aromatic structures, named "aromatization factor" ✓
Card 1/4

S/068/60/000/010/001/001
E071/E435

On the Utilization of High Boiling Coal Tar Fractions for the
Production of Carbon-Black

($A=K_oCa$) was conditionally taken as the main physico-chemical characteristic of the raw materials. This index at $Ca \leq 85\%$ characterizes the influence of the chemical composition of the raw material on the yield and properties of carbon black. Testing of coal-tar oils for the production of anthracene carbon black was carried out on an experimental plant with a throughput of 10 kg/hr under the following conditions: consumption of coke-oven gas for the carburization of oils - $10 \text{ m}^3/\text{kg}$; the temperature of carburized mixture - 360 to 380°C ; the distance between burners and precipitating surface - 46 mm ; overflow of tar from the carburettor - 6 to 9% on the starting raw material. The experimental samples of carbon-black did not differ substantially in their physico-chemical and physico-mechanical properties and corresponded to the requirements of GOST 7885-56. The yields of carbon-black from the individual oils are given in Table 2. Testing of the oils for the production of active furnace carbon-black was carried out on a pilot plant NIIShP, described in Ref.5.



Card 2/4

S/068/60/000/010/001/001
E071/E435

On the Utilization of High Boiling Coal Tar Fractions for the
Production of Carbon-Black

Technological conditions were kept the same for all types of raw materials; throughput was 20 kg/hr with an air consumption of 6.5 m³/kg, the temperature of the process varied from 1200 to 1300°C depending on the type of raw material. The experimental results are given in Table 3. It was found that coal tar oils in 79 to 92% consist of di- and tri-cyclic aromatic hydrocarbons. The most aromatized is pitch distillate. The yield of active anthracene carbon-black increases with increasing number of rings in the molecule and the content of aromatic carbon in the raw material. Anthracene fraction and pitch distillate present a high-quality raw material for the production of active anthracene carbon-black. The yield, specific surface and oil number of active furnace carbon black increase with increasing number of rings in the molecule and the content of carbon in aromatic structures of the raw material. In order to obtain moderately structurized carbon-black (more suitable for rubber than highly structurized black) absorption creosote oil, anthracene oil, anthracene fraction and mixtures of pitch distillate and

Card 3/4

S/068/60/000/010/001/001
E071/E435

On the Utilization of High Boiling Coal Tar Fractions for the
Production of Carbon-Black

anthracene fraction II with petroleum oils can be used.
There are 3 tables and 5 references: 3 Soviet, 1 English and
1 German.

ASSOCIATIONS: UKHIN, Gluzman, L.D.;
Nauchno-issledovatel'skiy institut shinnoy
promyshlennosti (Scientific Research Institute of the
Tyre Industry) Gilyazetdinov, L.P.;
Kadiyevskiy sazhevy zavod (Kadiyevka Carbon Black
Works) Molchanov, B.A.

Card 4/4

S/068/61/000/001/001/001
EO71/E235

AUTHORS: Gluzman, L. D., Nikitenko, A. G. and Tsin, R. M.

TITLE: Production of Technical Pyrene

PERIODICAL: Koks i khimiya, 1961, No. 1, pp. 52-55

TEXT: Pyrene is one of the important raw materials for the production of dyes and for this reason, the authors carried out an investigation of the potential resources, methods of separation and treatment of narrow pyrene fraction suitable for the preparation of products of various qualities from coal tar. In the USSR the coal tar is treated mainly on continuous plants for the production of a standard medium temperature pitch. The production of a high temperature pitch is done not by steam distillation, but by oxidation with air. Therefore, the raw materials for the production of pyrene are not "steam" but "air" pitch distillates. The pitch distillates (from the Zaporozh'ye Coking Works) taken for the investigation had the following properties: s.g. 1.120 at 20°C, pyrene content 4.85%; beginning of boiling 140°, 10% at 280°, 19% at 300°, 30% at 336°, 40% at 355°, 52% at 382°, 60% at 393°, 72% at 410°, 80% at 421°C. The distillates were fractionated on a

Card 1/4

S/068/61/000/001/001/001
E071/E235

Production of Technical Pyrene

laboratory column equivalent to 13-15 theoretical plates. On distillation, two narrow pyrene fractions were collected: 1) 384-388°C amounting to 6.5% of the initial pitch distillate, containing 33.0% of pyrene and 2) 388-395°C amounting to 8% and containing 48.2% of pyrene. The raw pyrene fractions were submitted to recrystallisation from various solvents. Optimum results were obtained from 30% aqueous pyridine and 30% alcoholic solution of solvent naphtha. The crystallisation conditions and results obtained are tabulated. It was found that recrystallisation of raw pyrene fractions containing less than 40% of pyrene give a mixture of pyrene with fluoranthene, which cannot be further enriched by this method and repeated recrystallisations lead only to losses of pure products, e.g., after four recrystallisations of fraction containing 27% of pyrene a product containing about 45% of pyrene was obtained with pyrene recovery of 58.4%. Subsequent recrystallisations were ineffective. Fractions containing 40% and more of pyrene can be easily enriched to 75-80%. The more concentrated is the initial pyrene fraction, the more concentrated

Card 2/ 4

S/068/61/000/001/001/001
E071/E235

Production of Technical Pyrene

for the production of carbon black. The technological scheme for the production of technical pyrene is diagrammatically shown in the text. There are 3 tables, 1 figure and 7 references: 3 Soviet and 4 non-Soviet. ✓

ASSOCIATION: UKhIN

Card 4/4

5.3300

27069
S/080/61/034/003/010/017
A057/A129AUTHORS: Gluzman, L. D., Nikitenko, A. G.

TITLE: Concerning the question of fluoranthen separation

PERIODICAL: Zhurnal prikladnoy khimii, v. 34, no. 3, 1961, 626 - 628

TEXT: A method for the separation of fluoranthen from coal-tar pitch distillates or an anthracene oil fraction is described. According to data obtained in the institute of the present authors coal-tar contains about 3.5% of fluoranthen and the companion compound pyrene in an amount of up to 1%. Several methods for separation of fluoranthen and separation of the latter from pyrene are described, e.g., in publications by O. Kruber et al. [Ref. 1: Erdöl und Kohle, 9, 637 (1955)], P. P. Karpukhin and N. M. Slominskiy [Ref. 7: Koks i khimiya, 10, 41 (1938)], and J. Szuba [Ref. 8: Przem. Chem., 12, 6, 316 (1956)]. The method described by O. Kruber was successfully proved by the present authors. Only the use of fluoranthen for production of intermediates and dyestuffs is mentioned in literature. The present authors assume that fluoranthen could be used simultaneously with other aromatic hydrocarbons as raw material in the production of synthetic resins of the type based on anthracene, naphthalene etc., such as described by

X

Card 1/5

27069

S/080/61/034/003/010/017

A057/A129

X

Concerning the question of fluoranthene separation

Wegler. It is also stated that almost the whole processing of coal-tars in the USSR occurs by a continuous method producing a pitch with a softening point of about 70°C which is converted by "air oxidation" and not "steam treatment" to a high-melting (150°C) product. Therefore the method described by the Polish authors [Ref. 8; Przem. Chem., 12, 11, 610 - 616 (1956)] is not suitable for the USSR, and in the present experiments only "air-oxidized" coal-tar pitch distillates and anthracene oil fractions were investigated (Table 1). The experiments were carried out under the assistance of T. A. Davydova. The pitch distillates were rectified on a 2 m column (diameter 40 mm) with an efficiency of 13 - 15 theoretical plates, at atmospheric pressure, and the fraction boiling at 370 - 385°C was withdrawn with a 5.7% yield containing 68% fluoranthene. From anthracene oil II the yield of the fluoranthene fraction was 14.5% with a fluoranthene content of 75% and a pyrene content of 21%. These fractions were recrystallized from ethanol, methanol, white spirit, pyridine, 30% pyridine, solvent, a mixture of 30% solvent and 70% ethanol, toluene, xylene or gasoline. Best results were obtained with the 30% aqueous solution of pyridine, gasoline and the mixture 30% solvent + 70% ethanol. (Table 2). If the ratio fluoranthene : pyrene is 3.5 : 1, a third recrystallization is necessary giving only a 15 - 25% fluoranthene yield. Anthracene oil II is a better raw

Card 2/5

27069

S/080/61/034/003/010/017

A057/A129

Concerning the question of fluoranthene separation

material than the coal-tar pitch distillates. After a threefold recrystallization a 99 - 100% fluoranthene (melting point 109.2°C) with a 4% yield in relation to the anthracene oil II was obtained. A technological scheme for the production of fluoranthene according to the present results is tested presently. There are 2 tables and 9 references: 3 Soviet-bloc and 6 non-Soviet-bloc. The references to the English-language publications read as follows: M. C. Kloetzel, Holly E. Mertel, J. Am. Chem. Soc., 72, 4786 (1950); Th. Holbro, J. Appl. Chem., 3, 1 - 9 (1953).

ASSOCIATION: Ukrainskiy nauchno-issledovatel'skiy uglekhimicheskiy institut (Ukrainian Scientific Research Institute of Coal Chemistry)

SUBMITTED: April 12, 1960

Card 3/5

S/081/62/000/014/023/039
B166/B144

AUTHORS: Molchanov, B. A., Gluzman, L. D., Gilyazetdinov, L. P.,
Chaykun, M. I.

TITLE: Pitch Distillate, a new form of raw material for the
production of carbon black

PERIODICAL: Referativnyy zhurnal. Khimiya, no. 14, 1962, 532, abstract
14M204 (Vestn. tekhn. i ekon. inform. N.-i in-t tekhn.-ekon.
issled. Gos. kom-ta Sov. Min. SSSR po khimii, no. 12, 1961,
23 - 24)

TEXT: Industrial test results for a trial batch of pitch distillate (PD) are given, this being got by oxidizing and coking coal-tar pitch to form a highly aromatized product used in the manufacture of carbon black. The industrial process for producing the carbon black is practically the same as when producing spray burner black from anthracene fraction. It is established that both these forms of carbon black have the same physico-chemical properties but the yield of the carbon black from PD is 2.3% higher. The experimental carbon black fulfils the requirements of

Card 1/2

Pitch distillate, a new form...

S/081/62/000/014/023/039
B166/B144

ГОСТ 7885-56 (GOST 7885-56). PD dissolves well at a temperature $\geq 50^{\circ}\text{C}$ in green oil and catalytic gas oil; the mixtures obtained are transportable. To avoid the burners coking up in continued operation it is expedient to use PD mixed with the anthracene fraction (mixtures with a small PD content have been tested). When 5 - 10% PD is added to green oil the yield of spray burner black is increased by 3%. PD is being introduced into the production of spray burner and lamp black to replace the anthracene fraction which is in short supply. Available stocks of PD also permit of its use for partly replacing green oil. [Abstracter's note: Complete translation]

✓

Card 2/2

GLUZMAN, L.D.; TSIN, R.M.; ROK, A.A.

Production of 2-vinylpyridine. Koks i khim. no.11:48-51 '61.
(MIRA 15:1)

1. Ukrainskiy uglekhimicheskiy institut.
(Pyridine)

S/081/63/000/004/028/051
B149/B186

AUTHORS: Gluzman, L. D., Leyba, V. S., Davidyan, D. N., Yefimenko, V. M.

TITLE: The preparation of diphenic acid from phenanthrene

PERIODICAL: Referativnyy zhurnal. Khimiya, no. 4, 1963, 461, abstract 4N78, (Sb. nauchn. tr. Ukr. n.-i. uglekhim, in-t.", no. 13 (35), 1962, 144 - 156)

TEXT: In order to develop an industrial method for the preparation of diphenic acid (I), a detailed study was made of liquid-phase oxidation of both pure and commercial grade phenanthrene (II) with H_2O_2 and CH_3COOH (III).

The reaction was performed under various conditions with successive alteration of the parameters affecting the course of the oxidation: ratio of II, H_2O_2 and III, concentrations of H_2O_2 and III, temperature, duration of H_2O_2 addition and duration of oxidation, and intensity of stirring during the addition of H_2O_2 and during auto-oxidation. The effect of various catalysts (such as $(NH_4)_2MoO_4$, $MgSO_4$, $MnSO_4$, $CuSO_4$, $KHSO_4$, CH_3COONa , $(CH_3COO)_2CO$, V_2O_5 , chrome-nickel alum and others), of different sorts of steel proposed
Card 1/3

S/081/63/000/004/028/051
B149/B186

The preparation of diphenic acid...

for the construction of the pilot plant [1X18H9T (1Kh18N9T) and 1X18H12M9T (1Kh18N12M9T)], of the quality of the initial II and its admixtures were investigated. The optimum conditions were found to be: ratio (in parts by weight) II:III:H₂O₂ (30%) = 1:5:3.2, temperature 90-92°, duration of oxidation 2 hrs. The period of addition of H₂O₂ has no effect on the yield of I. Stirring during the addition of H₂O₂ and during the reactions must be slow. The reaction can be achieved without catalysts (the ones listed above have no positive effect) with a 75-80% yield of I. The presence of anthracene (10-20%) and carbazole (2-5%) admixtures in II has no appreciable effect on the yield and quality of I. Optimum conditions for the isolation of I were found. The most complete isolation and highest degree of purity was achieved by: distillation of III under vacuum at 75% to 1/3 of the volume and cooling of the residue to 15°. The crystals which separate are washed on the filter with 10% solution of III. The yield of I (with m.p. ~228°) is 65-68%. The solubility of I in III, H₂C, CH₃COCH₃, dioxane, CH₃OH, C₂H₅OH, C₆H₆ and xylene was determined over the range 20-90° (the results are given in the form of graphs. For organic solvents, I is least soluble in C₆H₆ at

Card 2/3

The preparation of diphenic acid...

S/081/63/000/004/028/051
B149/B186

25° (10.16 g); the solubility is twice this in xylene. A method of regeneration of III has been developed. [Abstracter's note: Complete translation.]

Card 3/3

ACCESSION NR: AP4009235

S/0068/64/000/001/0038/0041

AUTHOR: Gluzman, L. D.; Ruzhina, I. Ye.

TITLE: Producing phenanthrene, fluoranthene, and pyrene under commercial conditions

SOURCE: Koks i khimiya, no. 1, 1964, 38-41

TOPIC TAGS: phenanthrene, fluoranthene, pyrene, commercial production, recovery, fractionation, anthracene oil, pitch distillate,

ABSTRACT: Plant-scale work at the Dnepropetrovsk Coke-Chemical Plant on recovery of phenanthrene, fluoranthene and pyrene by fractionating anthracene oil and pitch distillates confirmed earlier data from UKhIN that anthracene oil is the optimum crude for phenanthrene and fluoranthene, and pyrene is best recovered from pitch oil. Data are presented showing the conditions for separating the individual fractions, the amounts and the yields of the desired products. Orig. art. has: 4 tables.

Card 1/2

ACCESSION NR: AP4009235

ASSOCIATION: Dnepropetrovskiy khimicheskii zavod (Dnepropetrovsk Coke-Chemical Plant)

SUBMITTED: 00

DATE ACQ: 10Feb64

ENCL: 00

SUB CODE: MA

NO REF SOV: 004

OTHER: 000

Card 2/2

RUZHINA, I.Ye.; RASHKEVICH, I.Ya.; ITKINA, R.A.; GLUZMAN, L.D.;
Prinimali uchastiye: DEMCHENKO, L.G.; GOL'PERINA, R.L.

Curves of the single-stage evaporation and of the true temperatures
in the boiling of raw materials for pyrene production. Koks i khim.
no.3:48-52 '64. (MIRA 17:4)

1. Dnepropetrovskiy koksokhimicheskiy zavod (for Ruzhina,
Rashkevich, Itkina). 2. Ukrainskiy uglekhimicheskiy institut (for
Gluzman).

L 1962-66 ENT(w)/EPF(c)/EWP(j) RM

ACCESSION NR: AP5021785

UR/0068/55/000/008/0046/0049
668.74

AUTHOR: Stolyarenko, L. P.; Gluzman, L. D.

TITLE: Chemistry and technology of acenaphthylene production

SOURCE: Koks i khimiya, no. 8, 1965, 46-49

TOPIC TAGS: acenaphthylene, acenaphthene, dehydrogenation

ABSTRACT: To prepare acenaphthylene of high purity, the authors combined the method of catalytic dehydrogenation of acenaphthene with vacuum techniques. The effect of catalyst quality, reaction temperature, degree of vacuum, raw material quality, and presence of inert additives was investigated both under laboratory conditions and on larger batch-operated units. The industrial catalyst K-5 was found to be the best. The pressure has a marked influence on the dehydrogenation; the process is most complete when the residual pressure is 3-10 mm Hg. Addition of nitrogen as an inert carrier in the molar ratio of 8.4:1 raises the yield of acenaphthylene without improving its quality. Using the K-5 catalyst at a pressure of 8-15 mm Hg, the authors carried out the process in two variants: (a) concentration of acenaphthene -

Card 1/2

L 1962-66 ENT(m)/EPF(c)/ENP(j) RM

ACCESSION NR: AP5021785

UR/0068/65/000/008/0046/0049
668.7u

AUTHOR: Stolyarenko, L. P.; Gluzman, L. D.

TITLE: Chemistry and technology of acenaphthylene production

SOURCE: Koks i khimiya, no. 8, 1965, 46-49

TOPIC TAGS: acenaphthylene, acenaphthene, dehydrogenation

ABSTRACT: To prepare acenaphthylene of high purity, the authors combined the method of catalytic dehydrogenation of acenaphthene with vacuum techniques. The effect of catalyst quality, reaction temperature, degree of vacuum, raw material quality, and presence of inert additives was investigated both under laboratory conditions and on larger batch-operated units. The industrial catalyst K-5 was found to be the best. The pressure has a marked influence on the dehydrogenation; the process is most complete when the residual pressure is 3-10 mm Hg. Addition of nitrogen as an inert carrier in the molar ratio of 8.4:1 raises the yield of acenaphthylene without improving its quality. Using the K-5 catalyst at a pressure of 8-15 mm Hg, the authors carried out the process in two variants: (a) concentration of acenaphthene -

Card 1/2

L 1962-66

ACCESSION NR: AP5021785

dehydrogenation and (b) dehydrogenation - concentration of acenaphthylene. The latter procedure proved to be preferable. Recrystallization from ethyl or methyl alcohol was used to obtain high-purity acenaphthylene from the less pure product. Orig. art. has: 5 tables.

ASSOCIATION: UkhIN

SUBMITTED: 00

ENCL: 00

SUB CODE: GC

NO REF SOV: 003

OTHER: 009

Card 2/2